

Model	IPC-EB5500
Camera	
Image Sensor	1/3" 5Megapixel progressive scan CMOS
Effective Pixels	2592(H)x1944(V)
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual 1/3(4)~1/10000
Min. Illumination	0.01lux/F2.6(color) ,0.001Lux@F2.6(B/W)
S/N Ratio	More than 50dB
Video Output	N/A
Camera Features	
Max. IR LEDs	N/A
Length	
Day/Night	Auto(Electronic)/Color/B/W
Backlight Compensation	BLC/HLC/DWDR
White Balance	Auto/Manual
Gain Control	Auto/Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas
Lens	
Focal Length	1.42mm
Max Aperture	F2.6
Focus Control	Manual
Angle of View	H:185°
Lens Type	Fixed lens
Mount Type	Board-in Type
Video	
Compression	H.264/ MJPEG
Resolution	5M(2560'1920)/3M(2048x1520)/UXGA(1600x1200)/1.3M(1280x960)/720P(1280x720)/D1(704x576/704x480)/CIF(352x288/352x240)
Fram Main e Stream	5M(1~12fps)/ UXGA (1 ~ 25/30fps)
Rate Sub Stream	D1/CIF(1 ~ 25/30fps)
Bit Rate	H.264: 20K ~ 8192Kbps
Audio	
Compression	G.711a/G.711u/PCM
Interface	1/1 channel In/Out(Built in Mic)
Network	
Ethernet	RJ-45 (10/100Base-T)
Wi-Fi	N/A
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS, Bonjour
Compatibility	ONVIF,PSIA,CGI
Max. User Access	20 users
Smart Phone	iPhone, iPad, Android, Windows Phone
Auxiliary Interface	
Memory Slot	Micro SD, Max 64GB
RS485	N/A
Alarm	1/1 channel In/Out
PIR Sensor Range	N/A
General	
Power Supply	DC12V,PoE
Power Consumption	Max 6W
Working Environment	-30°C~+60°C, Less than 95% RH
Ingress Protection	N/A
Vandal Resistance	IK10
Dimensions	Φ110mm×54mm
Weight	0.25kg